

RainSoft turns ordinary water into extraordinary water . . .

- Rugged
- Reliable
- Effective

Acid Neutralizing System

Fully Automatic Whole-House Acid Neutralizer

A RainSoft Acid Neutralizing System is designed to help solve special water treatment problems and is built for long life and trouble-free operation.

Controls blue-green staining caused by the corrosion of copper pipes.

RainSoft
Environmental Products for the Home ...since 1953

2080 East Lunt Avenue
Elk Grove Village, IL 60007 USA
847-437-9400
1-800-RAINSOFT (USA only)
www.rainsoft.com

A Division of Aquion Water Treatment Products

Distributed by:

Castle Water, LLC
856 S. Washington St.
Greencastle, PA 17225
800-323-7321
www.castlewater.com

(Each RainSoft dealership is independently owned and operated.)



Filtration System Features

Tank-Within-A-Tank Construction Rugged tank is wound with miles of glass filament for extraordinary strength. Inside, there's another tank of sanitary plastic so your drinking water will never touch the fiberglass interior surface.

Exclusive Composite Valve Uses advanced NORYL™ composite material to enhance dimensional integrity and protect valve from expansion or shrinkage due to pressure and temperature demands.

Electronic Timer

Simple yet versatile controls. Set it and forget it; enjoy an unlimited supply of filtered water.

Power Outage Recovery If power is lost, the TC Series will automatically recover and complete the process once power is restored. This feature ensures that all scheduled regeneration cycles are never missed, and that filtered water is always available.

Powerful High Torque Motor Self-lubricating and with power to spare, for maintenance-free, long life operation.

Large Porting & Internal Piping The TC filter provides generous water flow rates.*

Manual Regeneration Tab A simple push of the tab starts a complete regeneration cycle giving you extra treated water if and when needed.

Automatic Bypass During Regeneration Eliminates the inconvenience of being without water.

NOTE: Tank size and local water pressure will affect the unit's operating flow rate.

CALIFORNIA RESIDENTS ONLY

Please note that your state certification information for this product is described on the back of the sheet.

The smart, economical way to enjoy the best water possible.

Choice of Filter Media

AZINUTE II This ground and graded, high alkaline granular material slowly dissolves in acid water. It's also easy to pour into the tank when replenishment is necessary. (Ported tanks only.)

AZINUTE II/SUPER AZINUTE BLEND Super Azinute is a processed, bead-like magnesia that is faster acting than Azinute II. This combination media should be used on water with very low pH.

AZINUTE III The smaller particle size of the Azinute III filter media provides the same benefits as Super Azinute, and prevents the media from solidifying thereby improving filtration.

Application Limitations

The rate of flow from the well pump must be greater than 6 gallons per minute (GPM) and the incoming hardness level must be less than 5 grains per gallon (GPG). Failure to have the proper backwash rate or exceeding the incoming hardness level will inhibit the filters ability to perform as designed. Frequent backwashing may be required depending on incoming water quality. Local water conditions will determine whether your dealer selects Azinute II or Super Azinute Blend filtering media for your application.*

Maintenance Requirements

The filtering media will eventually become exhausted or consumed and will need replacement. The replacement schedule will depend on the incoming water quality and the amount of water you use. Your local authorized RainSoft dealer can provide you with replacement schedules based on your water-using habits and your incoming water quality.*

The regeneration valve is designed to last a lifetime. From time to time it may be necessary to clean and lubricate the moving parts. Your water quality and the amount of regenerations necessary will affect this schedule. Your dealer is knowledgeable in different water qualities and the necessary parts required in completing this service.

CALIFORNIA RESIDENTS: Water treatment devices sold to retail consumers in California accompanied by certain health claims must be certified by the State of California Department of Public Health. The RainSoft TC-FLT Y, P Y, YZ and P YZ Series filters are not certified by the State of California for the purpose of making health claims.



TF-FLT models Y, P Y, YZ and P YZ are UL and CSA listed, and are certified by TÜV to meet European CE requirements. TF-FLT models P Y and P YZ are tested and certified by the WQA to Standard S-200. See the performance data sheet for specific reduction claims.

Benefits will be provided by various types of RainSoft equipment when installed and operated according to manufacturer's recommendations. Operational, maintenance and replacement requirements are essential for the product to perform as advertised. All claims based on best available information at time of printing. Manufacturer makes no representations as to the suitability of this equipment for a particular application. Buyer relies entirely on dealer's recommendations in the purchase of this equipment. Independent RainSoft dealers may include, together with your RainSoft product, a product or component that is not manufactured by RainSoft or their parent company, AWTP, LLC. Any non-RainSoft product may be covered by the manufacturer of that product, and is not covered by the RainSoft warranty. AWTP, LLC does not warrant that your RainSoft product and the non-RainSoft product will perform properly when used together, and assumes no liability therefore.

* The system will perform with hardness levels above 5 GPG. The bed life will be reduced based on the hardness level. Frequent backwashing will prolong bed life.